



Features

- All New Lightweight Aluminum Alloy Design
- Optional Intelligent Modularized Keypads
- Outdoor usage 3.5 inch High Resolution Touch Screen with LED backlight
- WinCE Net 5.0 for customized applications
- Built in GPS systems for global access and positioning
- Supports 3.5G wireless capability (including HSDPA)
- Supports 802.11b/g, (CCX4 certified)
- Supports Bluetooth 2.0 EDR
- Supports linear laser scanner, reads most common barcode symbologies
- IP65 rating drop tested at 5 feet (1.5m) off concrete floor
- 200 Pixel Camera with LED offers clearer images
- 500 dpi Fingerprint Scanner ensures higher security level
- Large battery capacity at 13.69 Watts to ensure long hours operating time
- 320MB FlashROM and 128MB RAM for system and user's data storage the largest memory capacity in its class

Operation System

| | |
|--------|----------------------------------|
| CPU | Intel PXA270 520MHz |
| Memory | SDRAM: 128MB Flash ROM: 320MB |
| OS | WinCE.NET5.0 |

Display

240x320 QVGA, Color Transflective TFT, with Touch Screen & backlight

Keypad

Modularized keypad 24-Key in default package, including numeric key, alpha key and function key
43 keys keypad is optional

Input Device

Keypad, Touch Screen, Full Alphanumeric Software Keyboard and Bar Code Scanner Fingerprint scanner(optional) 500DPI / 256 grey scale
Camera 2.0M pixel

Indicator

LEDs, Vibrator

Symbologies

1D Barcode Engine

UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCII, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba

2D Imager (optional)

1D codes Australian post, British post, Canadian post, Codabar, Code 11, Code 128, Code 39, Code 93, EAN 13, EAN 8, IATA 2 of 5, ITF, ISBT, Japanese-post, Kix code (nl), Korean post, Matrix 2 of 5, MSI, Planet code, Postnet, RSS expanded, RSS limited, RSS 14, UPC A, UPC E, UPC E1

2D codes Aztec, Codablock F, Code 49, Datamatrix, EAN-UCC, composite, Maxicode, Micro PDF417, PDF 417, QR code, Tcif lonked C39

Communication

USB 1.1 Host & Client
WLAN IEEE 802.11b/g, (CCX4 certified)
PAN Bluetooth 2.0 EDR
WWAN 3.5G Five-bands ,GSM/GPRS 850Mhz , 900Mhz , 1800Mhz and 1900Mhz ,UMTS WCDMA/HSDPA 50Mhz,1900Mhz ,2100Mhz / GPRS Edge
GPS Sirf star III Chip set, Supporting Instant Fix™

Audio

MIC
Speaker
Headset Connector
Receiver

Power Source

Main Battery 13.69 Watts Li-ion battery pack
Backup Battery One rechargeable Ni-MH backup battery
Operation Hours Up to 10 hours, depending on configuration and application

Enclosure

Weight 500g
Dimension Approximately 199.5mm x 88mm x43.3mm (Antenna length excluded)

Environmental

Operating temperature 14 °F to 122 °F (-10 °C to 50 °C)
Storage temperature -4 °F to 140 °F (-20 °C to 60 °C)
Relative Humidity 5% ~ 95% (non-condensing)
Drop test to Concrete 1.5 meter
Environmental Sealing IP65

Software

Microsoft Visual Studio 2005
Microsoft Windows CE 5.0 SDK (from unitech)
Oracle Database Lite
Narigator (US, Canada, Europe area)

Software

Desktop USB Cradle
USB communication and charging cable
AC adaptor (with regional power cord)
Vehicle Cradle
Battery charger
4 slot Multi-Bay Ethernet Cradle

Regulatory Approvals

CE, FCC, BSMI, VCCI, CCC, RoHS compliance



Unitech electronics co., ltd. / www.unitech-adc.com / marketing@tw.ute.com

Global Operation

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan